



REV	ECN	DESCRIPTION	BY/DATE	CHK	APPR
C	8060	ADDED NOTE 2: THREAD RELIEF SURFACE MAY HAVE PORTION OF THREAD MINOR DIAMETER VISIBLE	RLA 11/11/11	JS	DV
D	8962	NOTE 1 IS: MATERIAL: STAINLESS STEEL. WAS: MATERIAL: STAINLESS STEEL PER NAS1352N08H12 OR EQUIVALENT.	AB 08/08/12	QA	

2 THREAD RELIEF SURFACE MAY HAVE PORTION OF THREAD MINOR DIAMETER VISIBLE

1 MATERIAL: STAINLESS STEEL.

EXCEPT AS OTHERWISE NOTED	
ALL DIMENSIONS IN INCHES TOLERANCE: .XXX = ± .XX = ± .01	
SURFACE FINISH EXCEPT AS NOTED ✓	
BREAK EDGES TO DEBURR RADIUS OR CHAMFER	
△ THESE DIAS ⊙ TO T.I.R.	
FILLETS - MAX RAD.	

		<h1>MASTER</h1> <p>ONLY IF IN RED</p>		CHATSWORTH, CA.	
SCALE	4X	REV	DATE	ECN	
			SEE REV BLK		
DATE	9/4/97	PART NO.	6238A2		
DRAWN	N.C.	CHECKED	R.A.	MAT'L	SEE NOTE 1
APPROVED	DV 11/13/11	NEXT ASSEMBLY	USED ON		3168 SERIES
TITLE				DWG NO.	
OUTLINE DRAWING, MODEL 6238A2 CAPTIVE MOUNTING SCREW, 8-32 W/LOCKWIRE HOLES				127-6238A2	
SHEET				1 OF 1	